



Wingrove Marketing Pty. Ltd.

ABN 47 041 945 367 10 Meehan Place, Kirrawee NSW Australia 2232

Telephone 61 2 8539 7300 Facsimile 61 2 8539 7677

Email sales@wingrovetmarketing.com.au

Website www.wingrovetmarketing.com.au

MS-UB Connector



The Ergonomic Tap Splice Connector

This gel-filled moisture resistant UB tap splice connector (Blue lid), features space saving design. Its pre-crimp feature allows an electrical contractor to position the UB and snap it into place with their fingers before final crimping. The pre-crimp prevents the possibility of the wire slipping out of the connector before the tool crimp is made, making it a more effective and efficient splicing connector.



The UB also allows you to tap directly into an existing wire without interrupting service. In ready access closures the UB eliminates cutting cable pairs, open ends and piecing out wires.

The UB accepts 22 (0.7mm) through 26 (0.4mm) AWG paper, pulp and PIC air core or 24 (0.5mm) through 26 (0.4mm) AWG PIC filled core cable.

Technical Information

- Gel-filled IDC
- Insulated tap connector for solid-copper conductors of 22 to 26 AWG having maximum O.D. of 1.52 mm
- Simple crimp connection using the MS-Crimping Tool for fast, easy and reliable installation
- Moisture resistant sealant, rated to IP 67
- Dust resistant
- Immersible up to 1 metre
- Dielectric strength 3.0KV min (at 60HZ AC test voltage and a rate of 500V (RMS)/sec)
- High humidity insulation resistance of 105 M-ohm minimum
- Water immersion insulation resistance 100M-ohm minimum
- Connection resistance change is 2M-ohm maximum (after testing for vibration)

Connector UB	
Maximum Insulation O.D.	
Metric (mm)	1.52
Inches	0.060
Cable Type PIC-unfilled and PIC-filled, Pulp or Paper	
AWG	22-26
Metric (mm)	0.6-0.4
Ordering Information	
Gross Weight (net in kg)	7.50 (5.5)
Packing Size (cm)	33x26x25
Package Quantity	100 pcs/small box 500 pcs/small bag 1,000 pcs/box 5,000 pcs/bulk bag 10,000 pcs/carton



Exclusive Representative for



MAINSTRING CO., LTD.

Hsin Ying Industrial Area
Suburb No 2, Shin Yea Street, Hsin Ying,
Tainan, Taiwan R.O.C.

Australian TM application 1102134 & 1102146
New Zealand TM application 743940 & 743944



Wingrove Marketing Pty. Ltd.

ABN 47 041 945 367 10 Meehan Place, Kirrawee NSW Australia 2232


Telephone 61 2 8539 7300 Facsimile 61 2 8539 7677

Email sales@wingrovemarketing.com.au

Website www.wingrovemarketing.com.au

MS MAINSTRING IDC Gel Connectors for Communication Applications

ORDERING INFORMATION			
MS Insulation Displacement Connectors for Communication			
Product ID	Part No.	Inner Unit Pack	Wholesaler Order Qty
MS-UB	MS-UB-100B	100/box	1,000 box
	MS-UB-500B	500/bag	5,000 bulk bag
	MS-UB-1000B	1,000/box	10,000 carton
MS-UB-Dry	MS-UBD-100B	100/box	1,000 box
	MS-UBD-500B	500/bag	5,000 bulk bag
	MS-UBD-1000B	1,000/box	10,000 carton



Crimping Tool

The crimping tool is small, light weight, easy-to-handle and economical. It has stepped jaws that provide a nearly parallel crimping action at time of connection.

The crimping tool also features side wire cutting and insulated handles. It is designed for use with UR, UB and UY connectors.

Ordering Information	
Gross (Net) Weight	11.4 (10.4) kg Per carton
Packing Size	37x31x19 cm Per Carton
Package Quantity	1/bag 6/box 72/carton



ORDERING INFORMATION			
MS Insulation Displacement Connectors for Communication			
Product ID	Part No.	Inner Unit Pack	Wholesaler Order Qty
MS-Crimping Tool	MS-CTool-6B	1/bag	6/box
	MS-CTool-72B	6/box	72/carton

Exclusive Representative for



MAINSTRING CO., LTD.

Hsin Ying Industrial Area
Suburb No 2, Shin Yea Street, Hsin Ying,
Tainan, Taiwan R.O.C.

Australian TM application 1102134 & 1102146
New Zealand TM application 743940 & 743944